


Starter Bearing



| select | Inquiry | Bearing No | Boundary Dimensions(mm) | | | | Basic Load Rating(N) | | Speed Limit RPM | Weight Kg | Type |
|------------|---------|------------|-------------------------|------|-------|-------|----------------------|------|-----------------|-----------|------|
| | | | d | D | B | r min | Cr | Cor | | | |
| 608-2RDA | 8 | 22 | 7 | 0.30 | 3350 | 1400 | 32000 | 0.02 | A | | |
| B800-2RDA | 8 | 23 | 24 | 0.30 | 3300 | 1370 | 34000 | 0.03 | B | | |
| B874-2RDA | 8 | 22 | 11 | 0.30 | 3300 | 1370 | 34000 | 0.03 | C | | |
| B879-2RDA | 8 | 23 | 11 | 0.30 | 3300 | 1370 | 34000 | 0.03 | C | | |
| B885-2RDA | 8 | 23 | 14 | 0.30 | 3300 | 1370 | 34000 | 0.03 | C | | |
| 629-2RDA | 9 | 26 | 8 | 0.30 | 4550 | 1960 | 30000 | 0.02 | A | | |
| 6000-2RDA | 10 | 26 | 8 | 0.30 | 4550 | 1960 | 29000 | 0.02 | A | | |
| 62000-2RDA | 10 | 26 | 10 | 0.30 | 4550 | 1960 | 26000 | 0.02 | A | | |
| 6200-2RDA | 10 | 30 | 9 | 0.60 | 5100 | 2390 | 25000 | 0.04 | A | | |
| B1046-2RDA | 10 | 23 | 11 | 0.30 | 2700 | 1270 | 32000 | 0.02 | C | | |
| B1050-2RDA | 10 | 27 | 11 | 0.30 | 4570 | 1970 | 30000 | 0.03 | C | | |
| B900-2RDA | 10 | 27 | 14 | 0.30 | 4570 | 1970 | 30000 | 0.03 | B | | |
| 6001-2RDA | 12 | 28 | 8 | 0.30 | 5100 | 2390 | 26000 | 0.02 | A | | |
| 6201-2RDA | 12 | 32 | 10 | 0.60 | 6100 | 2750 | 22000 | 0.04 | A | | |
| 62201-2RDA | 12 | 32 | 14 | 0.60 | 6100 | 2750 | 22000 | 0.05 | A | | |
| 6301-2RDA | 12 | 37 | 12 | 1 | 9700 | 4200 | 20000 | 0.06 | A | | |
| B2011-2RDA | 12 | 35 | 18 | 0.60 | 6106 | 2770 | 22000 | 0.07 | A | | |
| B2012-2RDA | 12 | 32 | 10 | 0.60 | 6820 | 3060 | 22000 | 0.04 | C | | |
| R8-2RDA* | 12.70 | 28.58 | 7.94 | 0.40 | 4040 | 1750 | 19000 | 0.02 | A | | |
| 6002-2RDA | 15 | 32 | 9 | 0.30 | 5600 | 2840 | 22000 | 0.03 | A | | |
| 6202-2RDA | 15 | 35 | 11 | 0.60 | 7750 | 3600 | 19000 | 0.05 | A | | |
| 6302-2RDA | 15 | 42 | 13 | 1 | 11400 | 5450 | 17000 | 0.09 | A | | |

Starter Bearing

| | | | | | | | | | |
|------------|----|----|----|------|-------|------|-------|------|---|
| B1583-2RDA | 15 | 47 | 18 | 0.30 | 13460 | 6485 | 17000 | 0.14 | A |
| B2021-2RDA | 15 | 35 | 13 | 0.60 | 7750 | 3600 | 19000 | 0.05 | A |
| B2022-2RDA | 15 | 38 | 19 | 0.60 | 7750 | 3600 | 19000 | 0.08 | A |
| B3021-2RDA | 15 | 43 | 13 | 1 | 11400 | 5450 | 17000 | 0.08 | A |
| B3022-2RDA | 15 | 46 | 14 | 1 | 13500 | 6550 | 16000 | 0.10 | A |
| B3031-2RDA | 15 | 47 | 14 | 1 | 13500 | 6550 | 16000 | 0.11 | A |
| B3041-2RDA | 15 | 52 | 16 | 1.10 | 16000 | 7938 | 14000 | 0.15 | A |
| 6003-2RDA | 17 | 35 | 10 | 0.30 | 6800 | 3350 | 20000 | 0.04 | A |